

ПРОДАЕТСЯ

Строительный лифт
Производство 2007 г., SCD 200/200 GD 090109.

Высота: 65 м

Нагрузка 1 тонна.

Цена 10,000,000 драм

Условия кредита

Условия кредитования до 10% предоплаты, 8% годовых, со сроком погашения до 5 лет









SC型施工升降机防坠安全器

特种设备型式试验合格证 TX F440-06-06 0005

型号 SAJ40-1.2 编号 **732820**

额定载荷 40 KN 额定动作速度 1.2 m/s

标定动作速度 **1.0** m/s

有效标定年限 2年 出厂日期 **200708**

昆山市东浦机械制造厂制造

厂址 昆山市蓬朗镇马塘 电话 0512-57611398

Operation Rules of SC/SCD-type Building Elevator

1. Drivers must be qualified and trained by the government department.
2. Should inspect steel cable, the electric apparatus, and safety devices before each part of employment organ works normally.
3. The lead of the machine (power) carried available to safety stop and power with the.
4. When elevators opening, strictly prohibit the passengers, the goods should not be taken out of the cage.
5. When elevators running, strictly prohibit the passengers to enter the bottom area or the top area of the cage.
6. If elevators do not work, the sound of red alarm should be heard, and stop in the middle and inspect, and strictly prohibit the passengers walk in the cage.
7. If heavy weather or force wind over 5 class, the elevators should not work, and stop the power and switch off.
8. The elevators should be checked daily (inspector, weekly inspection and monthly maintenance) and the tripper should be tested every three months for full load test.
9. When shift-changing, driver must complete records, when off duty, stop the page to make the bottom cage, and switch off.

Parameter Table of SC/SCD-type Building Elevator

Product applied standards: GB10060-2011 GB10069-2008
 Date: 2012.10.11

Item	Unit	SC100	SC100-2	SC100-3	SC100-4	SC100-5	SC100-6
Type	kg	1000	1000-2	1000-3	1000-4	1000-5	1000-6
Rated Load	person	12	12x2	12x3	12x4	12x5	12x6
Personnel in cab	mm	1x1x1.5	1x1x1.5	1x1x1.5	1x1x1.5	1x1x1.5	1x1x1.5
Headroom of transmission cage (length x width x height)	mm	150	150	150	150	150	150
Use height	m/min	30	30	30	30	30	30
Elevating speed	m/min	3.0	3.0	3.0	3.0	3.0	3.0
Governor type	kg	1000	1000	1000	1000	1000	1000
Weight suspension speed	kg	0	0	0	0	0	0
Counterweight weight	kg	130	130	130	130	130	130
Standard weight	mm	1500	1500	1500	1500	1500	1500
Standard Use Length	KW	2x0.5x1	2x0.5x1	2x0.5x1	2x0.5x1	2x0.5x1	2x0.5x1
Power	KW	0.5	0.5	0.5	0.5	0.5	0.5
Power supply	KW	30	30	30	30	30	30
Cable pitch							

Manufacturer: Foshan Wanshi Elevator Co., Ltd.
 Address: No. 10 of Pingzhou Road, Shiqi, Wanshi, Foshan, Guangdong
 Post code: 528251
 Tel: 0757-86198121 86794026
 Fax: 0757-86271982

ConverseBank



Mobile: 098-49-44-55



E-mail: ManukyanArtur@conversebank.am



Address: Vazgen Sargsyan 26/1



Website: www.conversebank.am

